

REPORT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No. 2103038STO-112

EQUIPMENT

Equipment: Radio to RS485 ATB Protocol Converter
Type/Model: RDB9-2.4G
Manufacturer: WESTLINE sarl
Tested by request of: C-RAD Positioning AB

SUMMARY

Based on the assessment in this statement, the equipment is determined to comply with the following requirements without testing:

EN 50663: 2017
Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2014
NZS 2772.1:1999

Date of issue: May 2, 2021

Tested by:


Ala El-Haery

Approved by:


Björn Utermöhl

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Test report number	Date	Description	Changes
2103038STO-102	April 1, 2021	First release	--
2103038STO-108	April 26, 2022	Second release	Referral to updated test report and updated TX frequency range
2103038STO-112	May 2, 2022	Third release	Correction of transmitting frequency range declaration

CONTENTS

	Page
1 Client Information	4
2 Equipment	4
2.1 Identification of the equipment	4
3 Test Specifications	5
3.1 Standards	5
3.2 Additions, deviations and exclusions from standards	5
3.3 Decision rule	5
4 Summary	5
5 RF Exposure, single transmitter	6
5.1 Limits	6
5.2 Calculations.....	8
5.3 Results	8

1 CLIENT INFORMATION

This assessment has been done by request of:

Company	C-RAD Positioning AB Sjukhusvägen 12 K 753 09 Uppsala Sweden
Name of contact	Johan Bostedt Phone +46 70 6576470
Manufacturer	WESTLINE sarl 20 rue du Buisson Richard 78600 Le Mesnil le Roi FRANCE

2 EQUIPMENT

2.1 Identification of the equipment

Equipment:	Radio to RS485 ATB Protocol Converter
Type/Model:	RDB9-2.4G
Brand name:	WESTLINE
Manufacturer:	WESTLINE sarl
Transmitter frequency range:	2400 – 2483,5 MHz
Measured output power eirp ¹ :	-1,0 dBm
Declared output power eirp ² :	0,0 dBm
Antenna gain ² :	0,0 dBi
Measured duty cycle:	96,4%
User separation distance:	5mm
Exposure conditions:	☐ Controlled environment (occupational) ☒ Uncontrolled environment (general population)
Region of body:	☒ Head or trunk ☐ Limbs

¹Reference for measurement: Intertek test report 2103038STO-111

²Declared by C-RAD Positioning AB

3 TEST SPECIFICATIONS

3.1 Standards

EN 50663: 2017: Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz)

EN 62479:2010, Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2014

NZS 2772.1:1999 Radiofrequency fields – Maximum exposure levels – 3 kHz to 300 GHz

3.2 Additions, deviations and exclusions from standards

No additions, deviations or exclusions have been made from standards.

3.3 Decision rule

The statements of conformity are reported as:

Passed – When the measured values are within the specified limits.

Failed – When one or more measures values are outside the specified limits

4 SUMMARY

The evaluation has been carried out at the Intertek Semko AB premises in Kista, Sweden.

The results in this report apply only to sample tested:

Test	Result
RF Exposure, single transmitter	PASS
RF Exposure, multiple simultaneous transmitters	NA ¹

¹EUT only has a single transmitter or transmitters cannot operate simultaneously

5 RF EXPOSURE, SINGLE TRANSMITTER

Result:	PASS
----------------	------

5.1 Limits

Reference: COUNCIL RECOMMENDATION of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) 1999/519/EC: Annex 2 Basic restrictions

Guideline / standard	SAR limit, SAR _{max} W/kg	Averaging mass, m g	P _{max} mW	Exposure tier	Region of body
199/519/EC	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs

Reference: Directive 2013/35/EU of the European Parliament and of the Council of 26 June 2013 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (electromagnetic fields): Annex III table A1

Guideline / standard	SAR limit, SAR _{max} W/kg	Averaging mass, m g	P _{max} mW	Exposure tier	Region of body
2013/35/EU	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs

Reference: Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz, Table S1: Summary of compliance provisions for mobile or portable transmitting equipment.

Equipment parameters	Test exemption	Spatial peak SAR [Table 2 Occupational]	Spatial peak SAR [Table 2 General Public]
Aware user exposure			
Mean power < 100 mW	X		
Mean power < alternative low-power exclusion level of IEC 62479 for SAR _{max} = 10 W/kg	X		
Mean power > 100 mW & separation > 20 cm			
Otherwise		X	
General public exposure			
Mean power < 20 mW	X		
Mean power < alternative low-power exclusion level of IEC 62479 for SAR _{max} = 2 W/kg	X		
Mean power > 20 mW & separation > 20 cm			
Otherwise			X

Reference: NZS 2772.1:1999

Section 3.7.3: In some circumstances an RF exposure evaluation may not be required. This is the case with low-power devices whose nominal average RF radiated power does not exceed 20 mW and which do not produce exceptionally high instantaneous fields.

5.2 Calculations

EIRP: $Power\ to\ antenna\ (dBm) + Antenna\ gain\ (dBi) = EIRP\ dBm$
Declared EIRP = 0,0 dBm
Measured EIRP = -1,0 dBm

Conversion dBm to W:

Declared, EIRP: $1\ mW * 10^{\left(\frac{EIRP_{dBm}}{10}\right)} = +1,0\ mW$
Measured, EIRP: $1\ mW * 10^{\left(\frac{EIRP_{dBm}}{10}\right)} = +0,8\ mW$

5.3 Results

Standard	Reference for limit	Value	Unit	Limit	Result
EN 50663: 2017	EN 62479	1,0	mW	< 20	PASS
Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2014	Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz	1,0	mW	< 20	PASS
NZS 2772.1:1999	NZS 2772.1:1999	1,0	mW	< 20	PASS