

AXE20-X, AXE20-Y and AXE20-XY

The **AXE20-X**, **AXE20-Y** and **AXE20-XY** motorized lasers are precision alignment solutions for medical and industrial applications. The units create one or two remote-controlled adjustable laser planes by projecting high-quality red, green or blue laser lines. When combined with other similar units, this allows the creation of a 3D reference in the Cartesian space. The **AXE20-XY** crosshair model features two independently adjustable orthogonal laser planes.

Features

- High-accuracy positioning
- Single-plane or crosshair
- Radio or cabled PC remote control
- 3 degrees of freedom per plane: translation, tilt and rotation
- Dual laser: two laser lines modules of any color
- Flexible on-wall, in ceiling or on post mounting

Applications

- Patient setup and marking in the field of radiation therapy
- Alignment and calibration of machinery and industrial equipment
- Leveling and alignment for manufacturing processes
- Metrology and geometric measurements

Technical specifications

Power supply	100–240 V _{AC} @ 50/60 Hz
Power consumption	49 W max.
Internal voltage	12 V _{DC}
Operating humidity	≤ 80%, non-condensing
Operating temperature	15–30 °C
Dimensions (H×W×D)	205×220×107 mm
Weight (AXE20-X, AXE20-Y)	4.5 kg
Weight (AXE20-XY)	4.7 kg

Laser output*

Laser class	2
Output power**	< 1 mW
Focus range	1.5–7 m
Line width	≤ 1 mm @ 4 m
Line length	≥ 4 m @ 4 m

* with laser modules **WLCxxx-5-LGCP**, not included (see separate datasheet)

** measured on a 7 mm aperture at 100 mm

Mechanical

Adjustment accuracy	±0.1 mm @ 3 m
Translation range	0–20 mm
Translation resolution	2.5 µm/step
Tilt range	±2.2 deg
Tilt resolution	25 µm/m
Rotation range	±3.5 deg
Rotation resolution	40 µm/m

Connectivity

Physical layer	RS485 or radio*
Data rate	115200 Baud
Protocol	proprietary
5 V _{DC} output	100 mA max.

* with the **RDB9-2.4G** external adapter



External connections

The **AXE20** units embed a DB9 male connector for communication and an IEC/EN 60601-1 compliant 100–240 V_{AC} IEC inlet.

DB9 connector	Function
1	5 V _{DC} power supply output, 100 mA max.
5	Ground
8	RS485 L+ (high for logic 1, low for logic 0)
9	RS485 L- (low for logic 1, high for logic 0)

Related products

AXE900	Motorized long-range medical alignment laser
AXE900IRM	Motorized long-range MR alignment laser
AXE20F-XY	Manual alignment crosshair lasers
AXE20F-X	Manual alignment horizontal lasers
AXE20F-Y	Manual alignment vertical lasers
WLC635-5-LGCP	Modulated red laser-line module
WLC532-5-LGCP	Modulated green laser-line module
RDB9-2.4G	Radio to RS485 ATB protocol converter
USB RF-2.4G	Radio to USB ATB protocol converter
ISOUSB485	USB to RS485 isolated serial converter

Ordering codes

AXE20-X*	Horizontal-plane model
AXE20-Y*	Vertical-plane model
AXE20-XY*	Dual-plane model (crosshair)

* laser modules not included (see **WLCxxx-5-LGCP**)